



FLAT BOTTOM FRAC TANK

GET IN TOUCH



Jimmy 915-301-6751

✉ jkelgordo@gmail.com



John G. 915-222-2054

✉ salesjtrailer@gmail.com

Dimensions:

Length: 47' 2 1/2"; width: 8' 6"; Height: 9' 9"

Capacity: 500 BBL

Floor: 1/4" PL,

Floor support: 2, 4x6, 3/16" square tube

Walls:

1/4" PL solid welded;

Corrugated Steel;

Corrugations 24" on center

Roof: Flat top, 1/4" PL Solid welded

Drain / Fill:

4" Floor drain at rear end

4" Fill pipe (candy cane)

4" Suction line connection at front

6" Gel line with 6 - 1 1/2" sprayer outlets

8" flanged front manifold connection with turn down to floor sump

Manway:

20" Manway on front

24" Manway on the side in front of axle

1 Non-sealed hatch on roof



Pick up: Standard 5th wheel king pin

Welds: All continuous except substructure crossmembers

Axle, suspension and wheels:
30,000 lbs.

Spring Suspension

Air Brakes

11R x 22.5" Bias tires on Steel disk wheels

Access: Front

Stairway

Level Gauge

Tank pressure / Vacuum relief vent

Outside color: Primer - VP38, paint - enamel polyurethane A-76

Inside coating: Primer - International enviroline 2405 hybrid epoxy,

Color: Green, light gray

Options

Special sizes

Open top design

Fixed or removable steam coils

8" Exterior manifold assembly

Color by dealer's choice

Finish: Per customer specifications



CAMPO 51 T, NAMIQUIPA, CHIHUAHUA

MEXICO. C.P. 31978



www.pumatrailer.com.mx

2024