PROVIDE YOUR BUSINESS WITH PUMA TRAILERS









www.pumatrailer.com.mx

SPECS

Lenght: 40'

Est. weight: 13,800 lbs. plus or minus 3% **Capacity**:

20 cubic yards single Hopper

23 cubic yards with 8" bang boards

Gates:

Double gates with 3/16" (grade 50) plate

Air controlled

Electric control from cab

Manual control from ground

Hopper:

52" x 70" opening

Sides:

above bottom rail: 54" height, 10 gauge (grade 50)

Fifth wheel: Oscillating upper plate with king pin

Wheels: 8.25 x 24.5 (8.25 x 22.5)

Options: Steel and aluminum disc 8-hub piloted standard Tires: 11R x 24.5 radials (11R x 22.5) **Axles:**



30,000 lbs. each

5" tubular with 16 1/2" x 7" cam brakes and oil seals **ABS brakes: ABS brakes on one axle** Suspension: 4 spring 3 leaf Suspension (air ride optional) **Rear bumper: Push block with under-ride protection** Top rail: 6" x 4" x 3/16" A500'B (H.S.L.A.) Bottom rail: 6" x 4" x 3/16" A500'B (H.S.L.A.)



For more information please contact us

Jimmy 915-301-5751

jkelgordo@gmail.com

John G. 915-222-2054

salesjtrailer@gmail.com

CAMPO 51 T, NAMIQUIPA, CHIHUAHUA MEXICO. C.P. 31978